ESCUADRÓN 303 — LANZAS DEL ALBA

STANDARD OPERATING PROCEDURES

Document revision · 29 October 2026

VATSIM connection — vPilot

Before connecting, verify eligibility and applicable rules, aircraft at a parking stand, correct flight plan, callsign, current client, and audio. Open vPilot, authenticate with VATSIM credentials, check flight details, and connect. Communicate with ATC through VATSIM voice and assigned frequencies. Disconnect using the client procedure at the end.

IVAO connection — Altitude

Before connecting, verify eligibility and applicable rules, aircraft at gate/parking, and matching flight plan/callsign. Start Altitude, click OFFLINE, enter IVAO VID and website password, registered name, callsign, aircraft/MTL, and Tx/Rx voice, then connect. Confirm ONLINE, check available ATC, and tune the frequency. Do not connect on a runway or taxiway; do not slew the aircraft after connecting. Disconnect at the end.

Parallel communication systems

VATSIM: vPilot is the pilot client and manages VATSIM connection and ATC communication. IVAO: Altitude is the pilot client and provides IVAO connection and ATC communication. They are independent systems and both will be used according to the selected network; neither replaces the other. TeamSpeak 3/Discord are internal channels, not ATC channels. Always follow ATC instructions and the active network’s rules

Limits

Do not use vPilot to connect to IVAO or Altitude to connect to VATSIM. Do not conduct restricted activity unless expressly authorized by the network in use and within the approved scope. Internal procedures do not grant network privileges or authorization

Software sources: VATSIM/vPilot and official IVAO/Altitude documentation. Check current versions and manuals before installation.